

Tel +44 1942 265 700 consumergoods.uk@intertek.com intertek.com



FLAMMABILITY TEST REPORT

Report No.: LEI19093797A Date Received: 24/09/19 **Date Tested:** 30/09/19 Date Issued: 30/09/19

Company Name & Address: **BUTE FABRICS LTD**

> 4 BARONE ROAD **ROTHESAY** ISLE OF BUTE PA20 ODP

Contact Name: S McGROARTY

Sample Details

Order No.: 3253/1

Description: Woven Fabric

Ref. / Style No.: CF774 Colour: Red Quality: **STORR** Supplier: Bute Batch No .: 34378/01 Upholstery End Use:

Quoted Fibre Composition: 97% Pure New Wool / 3% Nylon

Retailer Not stated

Sample Description: Red coloured woven fabric

Test Method	Pre Treatment	Requirement	Result
BS 5852: Part 1: 1979, Ignition source 0 (Cigarette)	None	Compliance with Schedule 4 Part 1 (The cigarette test) of The Furniture and Furnishings (fire) (safety) Regulations 1988 (as amended).	Complies
Note: Fabric was submitted for test rather than the upholstery composite so as suggested by The Guide to the Furniture Regulations the cover fabric was tested for cigarette resistance using standard polyurethane foam (non-modified) as this will give the furniture manufacturer a good indication of its likelihood to pass the cigarette test for the finished article			
BS 5852: Part 1: 1979, Ignition source 1 (Match)	None	Compliance with Schedule 5 Part 1 (The match test) of The Furniture and Furnishings (fire) (safety) Regulations 1988 (as amended).	Complies

STEVEN OWEN (Technical & Operational Excellence Manager)

ANDREW HALLETT (Flammability Team Leader)

CAROLE SPOWART (Flammability Administrator)

GREGORY JAMES (Flammability Technician)

Test Specification

Report No.: LEI19093797A Page 1 of 2











Tel +44 1942 265 700 consumergoods.uk@intertek.com intertek.com



FLAMMABILITY TEST REPORT

Test Method: BS 5852: Part 1: 1979 as modified by Schedule 4 Part 1 & Schedule 5 Part 1 of

The Furniture and Furnishings (fire) (safety) Regulations 1988 (as amended).

Ignition Source: Ignition source 0: Filterless cigarette

Ignition source 1: Butane Gas flowing at 45ml/min @ 25°C.

Flame Application Time: 20±1 seconds

Side Tested: Face

Filling Specification

Filling Type: Polyurethane foam

Supplier / Grade: Carpenter / RP21130 unmodified

Size: 450 X 300 X 75mm (back) & 450 X 150 X 75mm (seat)

Density / Hardness: 20-22 kg/m³ / Type B, 130N

Pre-treatment / Durability Procedure

None

Conditioning

Prior to Testing: At least 72 hours in ambient indoor conditions, then at least 16 hours in an

atmosphere having a temperature of 20±5°C and a relative humidity of 50±20%

At Time of Testing: Temperature between 15°C & 30°C. Relative humidity between 20% & 70%

Test Results

"The following test results relate only to the ignitability of the combinations of materials under the particular conditions of test; they are not intended as a means of assessing the full potential fire hazard of the materials in use."

Ignition source 0 (Test 1):	The cigarette burnt out within 24 minutes, there was no flaming or progressive
	smouldering. (Pass)
Ignition source 0 (Test 2):	The cigarette burnt out within 25 minutes, there was no flaming or progressive smouldering. (Pass)
Ignition source 1 (Test 1):	Flaming ceased with the removal of the burner, there was no progressive smouldering. (Pass)
Ignition source 1 (Test 2):	Flaming ceased with the removal of the burner, there was no progressive smouldering. (Pass)

Conclusions

The composite tested meets the requirements of Schedule 4 Part 1 (The cigarette test) of The Furniture and Furnishings (fire) (safety) Regulations 1988 (as amended). **PASS.**

The fabric tested meets the requirements of Schedule 5 Part 1 (The match test) of The Furniture and Furnishings (fire) (safety) Regulations 1988 (as amended). **PASS.**

This report is made solely on the basis of your instructions and/or information and materials supplied by you. It is not intended to be a recommendation for any particular course of action. Intertek does not accept a duty of care or any other responsibility to any person other than the Client in respect of this report and only accepts liability to the Client insofar as is expressly contained in the terms and conditions governing Intertek's provision of services to you. Intertek makes no warranties or representations either express or implied with respect to this report save as provided for in those terms and conditions. We have <u>aimed</u> to conduct the Review on a diligent and careful basis and we do not accept any liability to you for any loss arising out of or in connection with this report, in contract, tort, by statute or otherwise, except in the event of our gross negligence or willful misconduct.







